

Twins Digi Pro 80 LED Kopflicht

I. Allgemeine techn. Daten

Lichtstärke:			
Einzel LED	200-290Lm		
Doppel-LED	440-580Lm		
Farbtemperatur	5000-5650K		
Farb Render Index :	RI > 80		
LEDWinkel:	54° (+-1)		
Leuchtstärke	1M	2M	5M
EINZEL	220Lux	56Lux	10Lux
DOPPEL	440Lux	110Lux	20Lux
Art:	Power LED		
Abstrahlwinkel:	50°		
Gewicht:	186g ohne Akku		
Akku:	Li-Ion Akku		
Leistung:	2 x 2000 mAh		
Betriebszeit:	1,5 h (Beide LED ein)		
Abmessungen:	52mm(L)x43mm(B)x116mm(H)		
Ladegerät::	100~240V AC, 50/60Hz		
Gleichspannungsausgang	7.2V		

II. Packungsinhalt

TWIN Digi Pro 80 LED Kopflicht	1 Stck
Li-Ion Akku 7.2V 2000 mAh	2 Stck
Bedienungsanleitung	1 Stck
Ladegerät	1 Stck
Auslegebügel	1 Stck

III.

Technical Parameter		Unit	Single Light	Twin Lights
Luminous Flux		Lm	220-290	440-580
Correlated Colour Temperature		K	5000-5650	
Colour Rendering Index			≥ R I 8 0	
Illumination	1M	Lux	220	440
	2M	Lux	56	110
	5M	Lux	10	20
Shooting Angle		°	54 ± 1°	
DC Voltage Range		V	5.5 — 8.4 Volt	
Current Range		A	0.66-1.00	1.36-2.05
Battery Runtime	FP550	hours	2.5	1.5
	FP750	hours	5	2.5
	FP950	hours	8.2	4.3
Life time		hours	> 10.000	
Temperature increase on shell	10 minutes	°C	15	15
	30 minutes	°C	19	22
	1 hour	°C	19	26
Net weight		g		
Gross weight		g		
Packaging Dimension		g	23x15x9.5	